IPv6 Essentials Reference Sheet v1.8)

	IPv6 Addressing	
Address Type	IPv6 Notation	Binary Prefix
Unspecified	::/128	00000 (128 bits)
Loopback	::1/128	00001 (128 bits)
Multicast	ff00::/8	1111 1111 xxxx xxxx
Link-Local	fe80::/10	1111 1110 1000 0000
Global Unicast (GUA)	2000::/3	001x xxxx xxxx xxxx
Unique Local (ULA)	fc00::/7	1111 110x xxxx xxxx
6to4 (tunnel)	2002::/16	
Teredo (tunnel)	2001:0000::/32	
IPv4-Mapped IPv6	0:0:0:0:0:ffff:a.b.c.d	
NAT64	64:ff9b::/96	
Documentation	2001:0db8::/32	

Well Known Multicast Addresses		
Address	Description	Scope
ff01::1	All Nodes Address	Interface-local
ff02::1	All Nodes Address	Link-local
ff01::2	All Routers Address	Interface-local
ff02::2	All Routers Address	Link-local
ff05::2	All Routers Address	Site-local
ff02::4	DVMRP Routers	Link-local
ff02::5	OSPF IGP Drothers	Link-local
ff02::6	OSPF IGP DRs	Link-local
ff02::9	RIPng Routers	Link-local
ff02::a	EIGRPv6 Routers	Link-local
ff02::c	Microsoft SSDP	Link-local
ff02::d	All PIM Routers	Link-local
ff02::12	VRRPv3	Link-local
ff02::16	All MLDv2 Routers	Link-local
ff02::1:2	DHCPv6 Servers/Agents	Link-local
ff05::1:3	DHCPv6 Servers/Agents	Site-local
ff0x::101	Network Time Protocol	Variable
ff02::1:ffxx:xxxx	Solicited-Node Address	Link-local

ICMPv6 Message Types		
128	Echo Request	
129	Echo Reply	
130	Multicast Listener Query	
131	Multicast Listener Report	
132	Multicast Listener Done	
133	Router Solicitation	
134	Router Advertisement	
135	Neighbor Solicitation	
136	Neighbor Advertisement	
137	Redirect Message	
138	Router Renumbering	
139	ICMP Node Information Query	
140	ICMP Node Information Response	
143	Multicast Listener Report (MLDv2)	
144	Home Agent Discovery Request	
145	Home Agent Discovery Reply	
146	Mobile Prefix Solicitation	
147	Mobile Prefix Advertisement	

IPv6 Address Shorthand Notation

2001:0db8:0006:1ab5:0000:0000:0000:ba11

remove leading zeros to achieve

2001:db8:6:1ab5:0:0:0:ba11

additional reduction by replacing consecutive fields of zeros with double-colon "::" option (can only be done once) to achieve

2001:db8:6:1ab5::ba11

IPv6 Header				
Version (4)	Traffic Class (8)	Flow Label (20)		
Payload Length (16)		Next Header (8)	Hop Limit (8)	
Source Address (128)				
Destination Address (128)				

Version: IP version number, 6 for IPv6

Traffic Class: Similar to IPv4 ToS field. Used by nodes to identify and distinguish between different classes or priorities of IPv6 packets


Flow label: Used by a source to label sequences of packets for which it requests special handling by the IPv6 routers

Payload Length: Length of the IPv6 payload (may also include

Payload Length: Length of the IPv6 payload (may also include extension headers)

Next Header: Identifies the type of header following the IPv6 header **Hop Limit**: Decremented by 1 by every router that forwards the packet **Source Address**: IPv6 address of the originator of the packet, will be a unicast address

Destination Address: IPv6 address of the intended recipient or final destination of the packet, can be unicast or multicast address



IPv6 Next Header Fields (Extension Headers)		
0	IPv6 Hop-byHop Option	
41	IPv6 encapsulation	
43	Routing Header for IPv6	
44	Fragment Header for IPv6	
50	Encap Security Payload (ESP)	
51	Authentication Header (AH)	
59	No Next Header for IPv6	
60	Destination Options for IPv6	

IPv6 Address Types
Link-Local – Automatically assigned per interface, not routable
Global Unicast Address (GUA) – Assigned by SLAAC, Stateful (DHCPv6), or manual, routable to Internet
Unique Local Address (ULA) – Assigned by SLAAC,
Stateful (DHCPv6), or manual, not routable to Internet, is routable within enterprise (like private address)
 Unicast – one-to-one (link-local, unique local, global)
Anycast – one-to-nearest (allocated from Unicast)

Multicast - one-to-many (also replaces broadcast)

Wireshark Display Filters for IPv6

ipv6 – all IPv6 traffic icmpv6 – all IPv6 ICMPv6 traffic dhcpv6 – all DHCPv6 traffic icmpv6.type == 133 – all router solicitations icmpv6.type == 134 – all router advertisements icmpv6.type == 135 – all neighbor solicitations icmpv6.type == 136 – all neighbor advertisements

www.teachmeipv6.com jeff.carrell@teachmeipv6.com

icmpv6.type == 137 - all redirect messages

IPv6 Neighbor Discovery Protocol

Neighbor Solicitation (NS) – Neighbor address resolution (similar to IPv4 ARP)
Neighbor Advertisement (NA) – Response to Neighbor Solicitation requests
Router Solicitation (RS) – Sent by nodes "looking" for IPv6 routers on-link
Router Advertisements (RA) – Sent periodically by routers and in response to RS
Duplicate Address Detection (DAD) – Sent to own Solicited-Node Multicast Address

IPv6 Essentials Reference Sheet v1.8 © 2020 Jeffrey L. Carrell